

# **Engine Complete KIT : DOHC 4VALVE**

(2SMS)

Secondary kick starter engine

124 cc (54 x 54)

TAF 5 speed

Special Clutch (dry / Hydraulic type) O / P

Item No. : 0 1 0 0 9 3 1 2

Compatible models

Monkey / Gorilla : Z50J -2000001 ~

: AB27-1000001 ~ 1899999

Thank you for purchasing our Complete Engine.

This engine is one of our Engine Complete Series which we have designed and produced by using with years of our experienced product development and manufacturing know-how.

We are proud of that we guarantee customer satisfaction with such a lightweight and high power engine.

Before installing and using this product, please check the contents of the kit, read this installation instructions carefully and understand them completely.

## **Important Notice**

- 1 . Please Note: Illustrations and photos may vary from actual hardware.
- 2 . The service and repair information contained in this manual is intended for use by qualified, professional technicians. Any person who does not have sufficient technique, knowledge, proper tools and equipment will never work. Be sure to ask specialty shops or professional mechanics.  
Poor technique and lack of knowledge may cause the maintenance problems or damage parts.
- 3 . This product is intended for use ONLY in closed racing course. Never use this product on public roads.
- 4 . This kit is compatible with the above mentioned compatible models ONLY. Note: Do Not use this product for other models than listed above.
- 5 . The cylinder length of this complete engine is longer than that of the stock engine.  
It is impossible to install on stock motorcycle chassis. NOTE: Modification of the chassis is required.
- 6 . Please note that mainly because of improvement in performance, design change, and cost increase, the product specifications and prices are subject to change without prior notice. We shall be held free and harmless from any and all liabilities or claims for any defects of the parts / the product after installation, and use, and/or any other products/parts.
- 7 . We do NOT accept any claims due to the parts for racing use only. Except, any requests for the return or repair of goods purchased from TAKEGAWA must be made within one month of receipt of goods against defects in workmanship and/or materials originally caused by ONLY our failure. No returns or repairs will be accepted after one month. However, we DO NOT accept our products which are NOT installed in the right way and/or DO NOT used properly.  
We are not responsible for any expenses for repair or replacements.  
NOTE: When you use for racing, we shall be held free and harmless from any and all claims.
- 8 . These instructions should be retained along with this product.,

## Read all instructions first before starting the installation.

We do not take any responsibility for any accident or damage whatsoever arising from the use of this product not in conformity with the instructions in this Manual.

While working on this product, be sure to proceed with the proper work in accordance with the instructions.

Be sure to prepare the genuine service manual of the compatible models and work as instructed. The service and repair information contained in this installation instructions and the genuine service manual are intended for use by qualified, professional technicians.

Be sure that any person who attempts service or repairs without the proper experiences, tools and equipment ask specialty shops or professional mechanics.


We shall be held free and harmless from any and all liabilities or claims for any defects of the parts/the product after installation, and use, and/or any other products/parts.

Do not use other manufacture's ignition parts, or it will cause the failure.


The necessary parts for this kit should be all TAKEGAWA-recommended parts. Always use our recommended parts.

Use TAKEGAWA-recommended fuel and engine oil.

Do not keep engine running in idle position for long period of time. It exceeds engine temperature, which cause the damage of the engine.

 **CAUTION** The following show the envisioned possibility of injuries to human bodies and property damage as a result of disregarding the following cautions.

- This Kit is designed for closed course competition purposes only. So please do not drive on a public road after the installation of this Kit.
- Before starting the installation, make sure the engine and muffler are cool at below 35 degrees Celsius. (Otherwise, you will burn you.)
- Prepare right tools for the work. (Otherwise, the installation with improper tools could cause breakage of parts or injuries to you.)
- As some products and frames have sharp edges or protruding portions, please work with your hands protected. (Otherwise, you will suffer injuries.)
- Always use new gaskets, seals and the like. The continued use of the worn or damaged ones will cause engine trouble.

 **WARNING** The following show the envisioned possibility of human death or serious injuries to human bodies as a result of disregarding the following warnings.

- Those who are technically unskilled or inexperienced are required not to do the work. (Improper installation because of insufficient skill or knowledge could lead to parts breakage and subsequently to accidents.)
- Before doing work, place the motorcycle on level ground to secure your motorcycle for safety's sake. (Otherwise, your motorcycle could overturn and injure you while you are working.)
- Always start the engine in a well-ventilated place, and do not turn on the engine in an airtight place. (Otherwise, you will suffer from carbon monoxide poisoning.)
- As gasoline is highly flammable, never place it close to fire. Make sure that nothing flammable is near the gasoline. (Otherwise it may cause a fire.)
- Tighten to a specified torque using a torque wrench. (Otherwise, improper tightening may cause the bolts or nuts to get damaged or come off, leading to accidents.)
- Never use the parts unspecified by us. (This may lead to parts breakage and consequent accidents)
- If you find damaged parts when checking and performing maintenance of your motorcycle, do not use these parts any longer, and replace them with new ones.  
(The continued use of these damaged parts as they are could lead to accidents.)
- When you notice something abnormal with your motorcycle while riding, immediately stop riding and park your motorcycle in a safe place to check what has gone wrong.  
(Otherwise, the malfunction could lead to accidents.)
- Carry out inspection and maintenance of your motorcycle correctly according to the instructions and guidelines in the service manuals. (Use TAKEGAWA-recommended fuel and engine oil.)
- Fuel must always be high-octane gasoline. (Otherwise, troubles such as engine knocking may cause accidents.)
- When driving a bike, a driver must always wear a helmet securely. Otherwise, the driver is likely to be subject to death or serious injury in an accident.

## Features

### DOHC 4 valve

To have two overhead camshaft and two intake valve and two exhaust valve, it is possible enlarge the overall valve size. Also incorporated with direct lifter makes compact and lightweight as much as possible. Camshaft moves with semi-gear train and adjustable camsproket, which makes possible to adjust valve timing.

### Use of Plated Cylinder:

This cylinder is aluminum one-piece construction and the ceramic chrome plated inner wall allows the additional wear-resistance and the reduced friction loss. It also features both high gas tightness and durability.

### Use of Oil Jet:

We have installed the oil jet which works to jet-spray the oil to the rear side of the piston from crankcase oil line in order to cool the piston.

### Use of Dry Multiple-Disk Clutch:

Due to attached clutch outer on the mainshaft of transmission, reduce the friction and weight on the crankshaft, which increase engine durability and throttle response.

To hold higher power and torques of the engine enlarged clutch capacity (5-plate clutch) and using stiffer valve spring.

Using 6 dampers at primary driven gear, which reduce shock and increase durability.

Using paper type oil filter, which can deliver oil to the crankshaft directly with great filtration.

Easy check the oil by level window.

Can be installed oil cooler kit with optional oil filter cover with adaptor.

Located Clutch system outside of the case which cools engine and easy to maintenance and replace the clutch.

Smooth clutch operation with hydraulic systems.


### Use of close ratio transmission:

The close ratio transmission is designed to enable smooth shift up and down and cornering, and, moreover, effective transmission of engine power.

### Use of Lightweight Outer Rotor ACG

SS-outer rotor is equipped as standard .Rotor body is a compact design and it weighs 536g. The best ignition timing is set up exclusively for this complete engine and the quick response has been achieved.

~ Kit contains ~



No.	Part Name	Qty	Repair Part Item No.	In packs of
1	Engine COMP.	1		
2	Spark plug, ER8EH	1	NGK-ER8EH	1
3	Intake manifold	1	06171-D4H-T00	1
4	Socket cap screw, 6 x 20	2		2
5	Socket cap screw, 6 x 15	2		2
6	Norma Torro Band	1		1
7	Inlet pipe gasket	1		1
8	Exhaust pipe gasket	1	00-01-0064	2
9	Alumi special (5 g)	1	00-01-0001	1
10	Braided hose, 8 x 1 m	1	00-07-0070	1
11	Hose clamp, 13.1	2		2
12	Spark plug cap COMP.	1	00-01-1013	1
13	Plug Cap rubber	1	30701-D4H-T00	1
14	Plug cord joint	1	00-01-1012	1
15	High tension cord, 500 mm	1	00-01-1043	1
16	Hyper CDI	1	05-03-0003	1
17	Gasket set	1	06111-D4H-TN0	1
18	Plug socket, 13mm	1	00-00-0247	1
19	Ball point driver, 4 mm	1		
20	Clutch master cylinder Assy.	1	02-02-2104	1
21	Rear view mirror bracket, 8mm	1		
22	Rear view mirror bracket, 10m	1		
23	Clutch hose, 775mm	1	06-080-0007	1
24	Banjo (straight)	2	00-07-0006	1
25	Banjo bolt, M10 x 1.25	2	00-07-0007	1
26	Aluminum sealing washer, 10mm	4	00-07-0010	10
27	Insulation lock, 200mm	1	00-00-0179	10
28	Brake fluid BF-4 (200ml)	1	06-08-0019	1

Please order repair parts with the Repair Part Item No. Without the repair part item NO., we may not be able to accept your orders.

Some parts are only available as a set. In this case, please order them with the set number.

Main Reference Value	
Type	4-cycle gasoline
Displacement	123.7cc
Number of cylinder and arrangement	Horizontal single cylinder
Cooling method	Air-cooling
Valve train	DOHC (chain / gear drive)
Chamber design	Pentroof (Hemispherical) type
Bore and Stroke	54mm x 54mm
Compression ratio	12.6 : 1
Camshaft type	Intake 25 Exhaust 30
Valve timing:	(1mm lift)
Intake open	20 ° BTDC
closed	50 ° ABDC
Exhaust open	60 ° BBDC
closed	20 ° ATDC
Lubricating method	Combined use of force feed system & splash lubrication system
Pump type	Trochoid type
Capacity	0.8 liter
Fuel to be used	High-octane gasoline ( research method: over 97 octane value)
Ignition system	C.D.I. ignition
Spark plug	NGK-ER8EH
Starting method	Kickstarter system
Power transmission	
Clutch	Dry multi-disk
Operating mode	Hydraulic type
Transmission	Super touring 5-speed
Type	Constant mesh, 5-speed return
Gear ratio	
1st speed	2.357 (33 / 14)
2nd speed	1.611 (29 / 18)
3rd speed	1.190 (25 / 21)
4th speed	0.958 (23 / 24)
5th speed	0.807 (21 / 26)
rear-wheel-drive mechanism	
Type	Chain drive

Inspect and Adjust		
Items	Frequency	Refer to page
Clean and Inspect Spark Plug	Every 200km	P-C1
Inspect Valve Clearance	Every 500 ~ 600km	
Change Engine Oil	Every 1000 ~ 2000km	P-C1
Adjust and Inspect Carburetor	Each time	Depend on Carburetor type
Replace Oil Filter	Every 1500 ~ 2000km	P-C2
Adjust Clutch Cable	Every 250km	P-C2
Inspect Clutch Friction Disc	Every 1000km	See Service Manual
Inspect Piston and Piston Ring	Every 1000km	See Service Manual
Inspect Piston Pin	Every 2000km	See Service Manual
Inspect Crankshaft	Every 1000km	See Service Manual
Inspect Cylinder Head and Cylinder	Every 2500km	See Service Manual
Inspect Crankcase	Every 2000km	See Service Manual

Maintenance period in the table is a guideline. You might need to work more frequently depending on the motorcycle usage or condition.

We recommend more frequently maintenance than the maintenance period.

## ~ Precautions of Use ~

### About the specifications of motorcycle to equip

The cylinder length of this complete engine is longer than that of the stock engine.  
It is impossible to install on stock motorcycle chassis. NOTE: Modification of the chassis is required.  
For Monkey / Gorilla, modify the chassis if necessary after checking whether the installation is possible referring to the following parts and optional parts of P-D1 ~ D4.

Compatible Specifications Data Chart		
Front Fork	Stock fork (Inapplicable) × Spec Modification	Our 30 Upright Front Fork (See P-D4)
Tyre	—————→	Larger wheel (10-inch) is recommended according to the power increase.
Top Bridge / Steering stem	Stock fork (Inapplicable) × Spec Modification	Our Top Bridge & Stem Kit or Front Fork Kit 60mm Offset (See P-D4)
Rear Fork	—————→	We recommend the modification to match the front fork and tire size. (See P-D4)
Oil cooler	—————→	We recommend to use it according to the heat increase. (See P-D3)
Drive / Driven sprocket	Stock (Inapplicable) × Spec Modification	Final Gear Ratio 2.188 ~ 2.063 (for 10-inch) (See P-D2)
Oil catch tank	Need to Install	Equipped as necessary (See P-D4)
Exhaust system	Stock exhaust (Inapplicable) × Special exhaust	Special exhaust port design and mount. (See P-D4)

### About fuel:

Whenever regular gasoline is remaining in the fuel tank, always replace it with high-octane gasoline.

### About oil cooler:

The installation of this product increases the heat release value of the engine, set off by the increase in power. We recommend you, therefore, to install an oil cooler kit, for a long-time high-load running, which keeps oil at appropriate temperatures and prevents such troubles as oil film shortage at high temperatures.

In case you use the breather cap, be sure to use an oil catch tank at the same time.

Due to large displacement engine, blow- by gas volume may increase. Larger capacity catch can are highly recommended. (approx 500 cc)

### About upper limit of revolution:

Max rpm may vary by the camshaft and engine specification, always use taco meter to avoid over-rev the engine rpm.

124cc : Intake camshaft : 25

Exhaust camshaft : 30


Maximum rpm : 12000 rpm

Take note that engine racing and sudden acceleration, particularly in the 1st or 2nd gear, tend to exceed the upper limit of revolutions.

Over revolutions will result in nonsmooth revolutions of the engine, not only adversely affecting the engine life, but also possibly breaking the engine in the worst case.

An Engine NO. (Serial No.) is stamped on this engine as identification.

Please specify your Engine NO. when ordering repair part or contacting us.



Engine No.stamped here.  
2SMS-00001 ~

**SPECIAL PARTS TAKEGAWA** Co.,Ltd.

3-5-16 Nishikiorihigashi Tondabayashi Osaka Japan TEL:81-721-25-1357 FAX:81-721-24-5059 URL: <http://www.takegawa.co.jp>

## ~ Installation Instructions ~

Before starting the installation, please prepare the relative service manual and necessary tools for the motorcycle.


And prepare necessary optional parts as well. For details, please see the attached sheets.

Caution: This installation instructions are for the models which this complete engine can be equipped.

Please Note: Illustrations and photos may vary from actual hardware.

### Remove the engine:

Remove the engine and carburetor from the motorcycle referring to the service manual of your vehicle.




### Installation of engine:

Install the engine COMP. to the frame referring to the relative service manual for the motorcycle.

⚠ Caution : Be sure to follow the specified torque.

⚠ Warning : Do follow the instructions in the service manual.

**20 ~ 25N·m  
(2.0 ~ 2.5kgf·m)**



⚠ Caution : Be sure to follow the specified torque.

**Torque: 20 ~ 25N·m (2.0 ~ 2.5kgf·m)**


### Connect ACG:

Replace the CDI with the supplied CDI referring to the service manual of your vehicle.  
Connect the wire from Engine COMP and the coupler from the motorcycle.

If you set up the main wire harness as a racing purpose, connect the wires referring to the attached wiring diagrams.  
(See P-B6)

### Install clutch master cylinder:


Chose one of mirror bracket and using pin to assemble.



⚠ Caution : Be sure to follow the specified torque.

**Torque: 8N·m (0.8kgf·m)**

Not use brake switch on the master cylinder (you can remove it).




### Install clutch hydraulic line

#### (master cylinder side)

⚠ Caution : Be sure to follow the specified torque.

**Torque: 14N·m (1.4kgf·m)**

Install clutch line and banjo with sealing washer.  
(as shown)




#### (clutch side)

Attach the sealing washer, banjo and sealing washer in this order to the spot-face of the hydraulic clutch cover, and hand-tighten the banjo bolt loosely for now.  
And route the clutch hose to the left side master cylinder. And install the sealing washer, banjo and sealing washer in this order with the banjo bolt. When the routing of the oil hose is fixed, then tighten the banjo bolt and brake hose fitting to the specified torque.

⚠ Caution : Be sure to follow the specified torque.

**Banjo bolt : 15 N·m (1.5 kgf·m)**


**Hose fitting : 6 N·m (0.6 kgf·m)**




### Injection of brake fluid:

Remove the reservoir cap on the left side master cylinder to check that the bleeder screw and banjo bolt are tightened. And inject the brake fluid up to the upper limit of the reservoir on the left side master cylinder. And by pulling and releasing the clutch lever some times, fill the clutch system with the brake fluid.

Repeat this operation till no bubble blows out of the primary port in the reservoir, or to the extent that you feel resistance in moving the lever.  
Do not mix the different brands of brake fluids together to avoid chemical change.  
As the brake fluid will damage the paintwork, never let the fluid adhere to the hardware.



Attach a vinyl tube to the bleeder screw, and squeeze the clutch lever hard until its end touches the grip. And give half a turn to the bleeder screw to loosen it, and tighten it up again. Slacken your grip on the clutch lever slowly, and when the clutch is fully back at its original position, keep the lever untouched for a few seconds. Repeat this operation until no air bubble blows out of the vinyl tube.



When you are through with the air bleeding, add the brake fluid up to the upper level mark of the reservoir. And attach a diaphragm and reservoir cap.

And check the torque for tightening the bleeder screw.

⚠ Caution : Be sure to follow the specified torque.  
**Torque: 5 N·m (0.5 kgf·m)**

Fill the reservoir with brake fluid to the 6mm lower from upper level mark. Install the diaphragm and cover.

### Clutch lever free play:

Adjust by screw at the master cylinder.  
It doesn't change the distance to the lever.



### Inspection:

With the engine turned off, shift the transmission to the first gear. Then, check that the rear wheel rotates when you move the machine, squeezing the clutch lever, and that the rear wheel does not rotate when you have released the clutch lever.

### Installation of carburetor:

Route the supplied throttle cable along the frame just like the stock throttle cable was routed.

Pass the throttle cable through the lower throttle housing, and connect the inner cable to the throttle pipe.

And attach the throttle housing to the steering handle. Apply grease to the rubbing surface of the throttle pipe, cable end and the cable taking-up portion on the pipe.


Put a inlet pipe gasket between the cylinder head and the inlet pipe, and tighten it with 6x20 socket cap screw to the specified torque.

⚠ Caution : Be sure to follow the specified torque.  
**Torque: 10 N·m (1.0 kgf·m)**



Fasten the carburetor insulator, to be used on the inlet pipe, with the supplied two socket cap screws.

⚠ Caution : Be sure to follow the specified torque.  
**Torque: 10 N·m (1.0 kgf·m)**



In the case of PE28:

Fits only the Monkey


NOT installable onto the Gorilla

Remove a float chamber, and then a main jet.


Attach a supplied main jet #110 and slow jet #35, and then a float chamber.

Detach a top cover of the supplied carburetor, and pull out the spring and throttle valve.

Pass the inner cable of the throttle cable through the carburetor top cover and then through the spring. And compressing the spring, fix the top cover and all to the throttle valve. Fix the throttle valve to the carburetor by aligning a notch on the throttle valve with the throttle stop screw.




Insert the carburetor into the insulator, and fasten them with a clamp band.



Attach an air filter, which please secure by tightening a band.

Adjust the free play at the throttle grip to be about 5 mm by turning the adjuster of the throttle cable. Follow the instructions of your throttle cable to adjust the free play.




Snap the throttle a few times to make sure that the throttle moves smoothly without sticking and that the throttle valve is fully open. And check that the throttle has free play even when a steering handle is turned all the way to the right or to the left. Insert a fuel tube and fasten it with a tube clip. Open the fuel cock and check for oil leaks.



In the case of VM26:

Remove the top cover from the carburetor, and pull out the spring and the throttle valve.

Pass the inner cable of the throttle cable through the carburetor top cover and then through the spring. And compressing the spring, fix the top cover and all to the throttle valve. Fix the throttle valve to the carburetor by aligning a notch on the throttle valve with the throttle stop screw.




Insert the carburetor into the insulator, and fasten them with a clamp band.



Attach an air filter, which please secure by tightening a band.

Adjust the free play at the throttle grip to be about 5 mm by turning the adjuster of the throttle cable. Follow the instructions of your throttle cable to adjust the free play.



Snap the throttle a few times to make sure that the throttle moves smoothly without sticking and that the throttle valve is fully open. And check that the throttle has free play even when a steering handle is turned all the way to the right or to the left.

In the case of installation to any model of the Gorilla, replace the pre-installed fuel cock with the supplied cock. Adjust the direction of the fuel cock and fasten the nut to the fuel tank.

**⚠ Caution :** Be sure to follow the specified torque.  
**Torque: 5 ~ 6N·m (0.5 ~ 0.6 kgf·m)**



Insert a fuel tube and fasten it with a tube clip. Open the fuel cock and check for oil leaks.  
(Do not leave the cock open for many hours.)

Dispose of the blow-by gas from the crankcase by yourself.


(Some races and regulations stipulate the blow-by gas disposal.)

In sending back the blow-by gas to the carburetor, connect the blow-by hose with the union on the air-filter.

(See Optional parts chart on P-D1)


## Installation of drive chain

Remove three bolt and the generator cover.




Install the drive sprocket.

**⚠ Caution :** Be sure to follow the specified torque.  
**Torque: 12 ~ 15N·m (1.2 ~ 1.5 kgf·m)**



Install the drive chain referring to a genuine service manual or instruction manual for the relative rear fork.



**⚠ Warning :** Do follow the instructions in the service manual.



Apply "Alumi-special" paste on the top of the crankshaft (where goes to bearing on the cover) and install generator cover.

⚠ Caution : Be sure to follow the specified torque.

**Torque: 10 N·m (1.0 kgf·m)**



Install the change pedal.

⚠ Caution : Be sure to follow the specified torque.

### Install the exhaust system

Attach a supplied exhaust pipe gasket to the exhaust port.



Install an exhaust muffer according to the installation instructions of the relative exhaust muffer.

### Start engine


Check that the ignition key and gas cock are turned off.

Keep kicking the starter for a while till the engine oil circulates all around the engine.


Install the spark plug. Lightly apply the "Aluminum Special", the heat-resistant lubricating agent, to the threaded portion on the plug. And tighten the plug.

⚠ Caution : Be sure to follow the specified torque.

**Torque: 8 ~ 10N·m (0.8 ~ 1.0 kgf·m)**



Here, the work needs to be done to extend the ignition cord. Cut off the ignition cord about 10 cm from the ignition coil. Cut the supplied cord at a point after fixing how to route it, and connect the cord with a supplied cable joint in the following way.



Attach the supplied plug cap to the extended ignition cord, and replace the plug cap rubber with the supplied one.




Attach the plug cap to the spark plug. Thoroughly wipe off dirt and dust on the engine.

### Engine oil

Remove the cap and add 850cc of engine oil.




Referring to the chart below, choose the engine oil whose viscosity matches the region and outside temperature.



Install the oil inlet cap.

Install an optional kick starter arm.

⚠ Note : Be sure to follow the specified torque.




Turn on the gasoline cock and the ignition key. Pull a choke lever to start the engine. Gradually loosen your grip on the lever, and warm up the engine till the revolution becomes smooth. And then return the lever fully back to its original location. If the engine does not run idle after warming-up, or it runs idle at high revolutions, adjust the revolutions with the throttle stop screw.

⚠ Warning : Be sure there is adequate ventilation whenever you run the engine.

Stop the engine once.

Wait for a few minutes and keep the motorcycle level to the ground, and then check the oil amount with oil level gauge on right crankcase.



Always keep the oil to the specified level. (Use the same grade and brand oil.)

Check for malfunctions such as unusual sounds. If no malfunction is detected, do the setting of the carburetor. (See the attached sheet)

⚠ Warning : Be sure to do the work in a well-ventilated place.

After the adjustment or setting, carry out a shakedown about 30 to 50 km, and check the valve clearance again.

IN : 0.15 mm

EX: 0.15 mm (See the attached sheet)

⚠ Caution : Be sure to do the work when the engine is cool.

Carry out again a shakedown up to about 50 to 100 km.

After the shakedown, check for malfunctions such as unusual noises or blow-by gas.

(If there is any malfunction, disassemble the engine again to check each part.)

Be sure to proceed the inspection referring to the Owner's Manual. (Purchase the owner's manual if necessary.)

⚠ Caution : Never reuse parts which are not suitable for reuse.

⚠ Warning: Those who are technically unskilled or inexperienced are required not to do the work.

## Relevance of Front Fork and Tire


### 27 Upright Front Fork

For 10-inch tire, clamp the top bridge at the highest point of the front fork.



Before installing, make sure that no interference occurs when the front fork is fully bottomed.


If the interference occurs, use the low profile tire in order not to interfere.




### 30 Upright Front Fork

Clamp the top bridge at the highest point of the straight portion to avoid the tapered portion of front fork.

Before installing, make sure that no interference occurs when the front fork is fully bottomed.



Generator side		Bike side		機能	Function
黄1	Yellow 1	黄	Yellow	灯火用AC出力 (AC電源用)	Lighting AC output (for AC power)
黄2	Yellow 2	白	White	灯火用AC出力 (DC電源用)	Lighting AC output (for DC power)
緑	Green	緑	Green	メインアース (GND)	Main GND
青/黄	Blue/Yellow	青/黄	Blue/Yellow	パルスジェネレーター信号	Pickup pulse
黒/赤	Black/Red	黒/赤	Black/Red	点火用AC出力	Ignition AC output
若葉/赤	Light Green/Red	若葉/赤	Light Green/Red	ニュートラルスイッチコード	Neutral Switch



## How to Set the Carburetor

- When the carburetor does not match the engine and the engine fails, the engine failures are caused by either too dense or too lean air-fuel mixture.
- The engine failure symptoms for the engine are as follows:

When the air-fuel mixture is too dense:	When the air-fuel mixture is too lean:
<ul style="list-style-type: none"> <li>• The explosion sound with a dull thud continues intermittently.</li> <li>• The engine malfunctions further if you use the choke.</li> <li>• The engine malfunctions when you warm it up.</li> <li>• The engine works well if the cleaner is detached.</li> <li>• The motorcycle belches dense (or, black) exhaust gas.</li> <li>• The plug smolders, getting blackened.</li> </ul>	<ul style="list-style-type: none"> <li>• The engine overheats somewhat.</li> <li>• The engine starts working well If you use the choke,.</li> <li>• The engine does not accelerate well. (No smooth acceleration)</li> <li>• Revolutions change, generating weak power.</li> <li>• The plug burns white.</li> </ul>

Set the carburetor only after warming up the engine, and then test-drive. And use a plug with the right heat value.

Do the setting in the following manner, studying at what throttle opening position the engine starts failing.

### Jet needle (Throttle position at 1/4 - 3/4)

Whether or not the engine revolution is in proportion to the throttle operation

- When the acceleration is not smooth or even, make the air-fuel mixture dense.
- Make the air-fuel mixture lean when the engine revolution goes up heavily and belches black gas.

The mixture ratio at this throttle position can be adjusted by the location of E-ring in the grooves.

The air-fuel mixture becomes dense as the location of the E-ring moves down from the 1st to the 5th groove.



### Main jet (The throttle position at 3/4 - 4/4)

The air-fuel mixture ratio at this throttle position can be adjusted by changing the number of the main jet. The larger the main jet numbers, the denser the mixture ratio becomes.

In view of the engine and muffler specifications, select the most appropriate main jet to get the highest revolutions.

### Pilot jet (First of all, please adjust the air screw.)

- In case you have given more than three turns to the air screw to tighten it, use a pilot jet with a small number.
  - If you have tighten the air screw (clockwise) to the full, use a pilot jet with a larger number.
- Check whether you have made a right choice of the pilot jet by seeing if the engine starts up revolving smoothly from the idling to running at slow speed.
- When the engine revolves up unevenly, the pilot jet number is too small. (At idle)
  - When the motorcycle belches black exhaust gas and produces heavy exhaust sound, the pilot jet number is too big. (At idle)
  - After replacing the pilot jet, you need to readjust the airscrew.

### Air screw

The air screw adjusts the air mass flow at the time of engine's revolving at slow speed. (At idling)

- Give the air screw a right turn The air-fuel mixture gets dense.
- Give the air screw a left turn The air-fuel mixture gets lean.

Loosen the tightened air screw back to the 1.5-turn position. And then from this position, give to the airscrew a right or left turn of 1/4 to 1/2 till the engine revolves at the highest speed.

Loosen the idle stop screw till you get the steady idling revolutions. And once again adjust the position of the airscrew to get the highest revolutions.

### On how the barometric pressure, temperatures and humidity affect the setting:

- At highlands or at high altitudes, the barometric pressure and air density go down and the air gets into the carburetor in less amounts.  
This makes the air-fuel mixture dense which was adjusted at low altitudes.
- Under the weather conditions with very low temperatures, the air density increases, which makes the air-fuel mixture lean.
- Under the rainy and humid weather conditions, the air density decreases, which makes the air-fuel mixture dense.

Please be informed that, mainly because of improvement in performance, design changes, and cost increase, the product specifications and prices are subject to change without prior notice.

This manual should be retained for future reference.

## ~ Inspections and Adjustments ~

### ⚠ CAUTION

Be sure to use a torque wrench and strictly keep the specified torque.

### ⚠ WARNING


The inspections and adjustments are intended for use by qualified professional mechanics. Be sure that any person who does not have the proper technique, experiences and knowledge will never work.

#### Spark plug:



Detach a plug cap, and then a spark plug with a plug wrench.

With a wire brush or a plug cleaner, clear the plug electrode section of the accumulated residues. Check the plug gap with a thickness gauge. And when the gap deviates from the benchmark, adjust it by bending the electrode section.



#### Gap

Benchmark : 0.6 ~ 0.7 mm

Check if the electrode section is worn out, corroded or burnt-out, or its insulator is damaged. When necessary, change the spark plug. With a wire brush or a plug cleaner, clear the plug electrode section of the accumulated residues. Check the plug gap with a thickness gauge. And when the gap deviates from the benchmark, adjust it by bending the electrode section.

#### Standard

• NGK : ER8EH

#### Plug with high thermal value (Cold type)

• NGK : ER9EH

Apply a small amount of ALUMI SPECIAL on screws of spark plug. Tighten the spark plug and install the plug cap.

⚠ Caution : Be sure to follow the specified torque.

#### Oil Change:

Warm up the engine within a few minutes to normal operating temperature.

Prepare an oil container under the drain bolt.

And drain the oil while the engine is warm.



Install the drain bolt, and tighten it to the specified torque.

⚠ Caution : Be sure to follow the specified torque.

**Torque: 19.5 ~ 24.5 N · m (2.0 ~ 2.5 kgf · m)**

Remove the cap of oil inlet and add 750cc of engine oil.



Add the engine oil in the specified amount.

#### Recommended oil:

SAE 10W - 40 20W - 50

API class, SF grade engine oil


#### Oil amount:

When oil change ONLY : 750cc

When rebuilt the engine : 800cc

Referring to the chart below, choose the engine oil whose viscosity matches the region and outside temperature.


Relationship between temperatures and viscosity



Install the oil inlet cap.

Warm up the engine within a few minutes to normal operating temperature.


Stop the engine once. Wait for a few minutes and keep the motorcycle level to the ground, and then check the oil amount with oil level gauge on right crankcase.



Always keep the oil to the specified level. (Use the same grade and brand oil.)


## Change of Oil filters:

Unfasten two bolts on the oil filter cover, and detach the oil filter cover, oil filter and oil filter spring.



Check the O-ring in an oil filter cover, and change it when necessary.

Attach a new oil filter to the filter cover.



Place the oil filter spring at the protrusion on the right side crankcase cover.

Apply a thin coat of engine oil to the O-ring on the oil filter cover, attach an oil filter and oil filter cover, and tighten two bolts to the specified torque.


⚠ Caution : Be sure to follow the specified torque.

**Torque: 10 N · m (1.0 kgf · m)**




## Adjust valve clearance.


Remove L side cover and dowel pin(x3)





Remove cylinder head cover.



Remove L generator cover.




Turn the crankshaft counterclockwise and align the "T" mark with the index notch on the left crankcase, at the same time center cam gear "O" mark with the index notch on the left cylinder head.



Check the valve clearance by inserting the feeler gauge.

IN :  $0.15 \pm 0.02$  mm (Cold)

EX :  $0.15 \pm 0.02$  mm (Cold)




Use clean feeler gauge.

## Valve clearance adjustment.

Remove a cam gear and camshaft, then valve lifters and shims.

- Use a valve punner or valve lap to remove valve lifters.
- When you cannot easily remove shims, use a pair of tweezers or magnet.
- (Keep the removed lifters and shims in an orderly way so you can see where to reinstall them back.)
- Be sure to reinstall back the valve lifters at its original place.



How to figure out a size of new shims:

- Wipe off oil adhering to the shims. Measure the thickness of the shims with a micrometer, and take a note of it.

A : Thickness of the shims to be figured out

B : The valve clearance measured

C : The valve clearance to be measured

D : The thickness of the shim removed


$$A = (B - C) + D$$



The shim is set at 1.20 mm to 2.9 mm, evenly spaced at 0.025 mm apart.

It is possible to use genuine Honda valve shim.

\* Be sure to check the size of new shims with a micrometer whether or not it is correct.




## Valve Lifter Installation

Attach the new shims to the valve spring retainer. Degrease the valve lifter, and blow air into the shim-mounting portion of the valve lifter to clean the portion. Apply molybdenum disulfide solution to the sliding surface of the valve lifter, and attach it.

⚠ Caution : Be sure to install back the lifter in its original location.

Attach the camshaft, and check the valve clearance with the thickness gauge.

**For example**, you have got a right valve clearance when you can put in a thickness gauge at 0.15mm but not at 0.18mm.




Apply engine oil (or molybdenum oil) solution on the camshaft.



Camshaft installation.



⚠ Caution: Make sure IN and EX.



Align the cam sprocket and center cam with alignment as well as the top of the cam lobe. Then install parallel pin.

IN


⚠ Caution: Never fail to align the alignment marks.



⚠ Caution: Do not place the parallel pin in the wrong place.

EX




⚠ Caution: Be sure to align the alignment marks.



⚠ Caution: Do not place the parallel pin in the wrong place.




Check the align of the mark.




Install camshaft washer and tighten the cam sprocket bolt (5x12) to the specified torque.


⚠ Caution : Be sure to follow the specified torque.  
**Torque: 10 N · m (1.0 kgf · m)**



Clean and degrease case surface and install the dowel pin.




Install new head cover gasket.




Install head cover with screw, apply alumi-special paste on the screw and tighten to the specified torque.

⚠ Caution : Be sure to follow the specified torque.  
**Torque: 6 N · m (0.6 kgf · m)**




With a cutter knife, cut off the gasket squeezing out of the cylinder head side to make the surface flat.


⚠ Caution: Be careful not to scratch the side-cover mating surface.



Degrease well the side-cover mounting surface.



Install dowel pin on the head.



Attach the cylinder head left side cover to the cylinder head with nine 5x22 and two 5x15 cap screws. (See the foto below.)

Lightly apply "Alumi Special", the heat-resistant lubricating agent, to the threaded portion of the screws.

⚠ Caution: Be sure to fit the screws in the right positions.




Tighten each socket cap screw diagonally in a few steps to the specified torque.

⚠ Caution : Be sure to follow the specified torque.  
**Torque: 6 N · m (0.6 kgf · m)**



Re-install the generator cover and tighten to the specified torque.



⚠ Caution : Be sure to follow the specified torque.  
**Torque: 10 N · m (1.0 kgf · m)**



## Change the valve timing.

### Positions of Cam Gear and Dowel Pin:

Change of the position of a cam gear dowel pin will make it possible to change the valve timing. The lobecenter at each dowel pin position is as per the illustration below. However, as this is just for your reference only, figure out the exact angle with a timing protractor and dial gauge.



#### Caution:

Shifting of the pin position from the originally pre-set position will degrade the performance. If you would change the pin position, please always try to do so without changing the cam top position as per the above illustrations.

Those who are not familiar with the valve timing are required not to shift the position.

#### ⚠Caution:

When you adjust the valve timing with the head installed to the motorcycle, valve lifters sometimes fall off at the time you remove the camshaft at the exhaust side. If the valve lifters have fallen off, detach the head cover, and reinstall back the shims and valve lifters at the original positions.

### Valve Timing Adjustment:

Set the piston at the top dead center (TDC) position.

Attach the timing protractor to the crankshaft, and set the protractor dial at "0" and tighten the nut.

Recheck that the piston is at TDC.

(In case it is not right on the TDC, adjust it with a pointer.)

Timing protractor : Item No. 00-01-0062

Set a magnet base stand so the dial gauge is vertical to the cylinder head valve lifter surface.

At this point, pressing the dial gauge. And set the dial at "0".

(Use a special rod so the dial gauge rod does not interfere with the camshaft)

Rotate the crank shaft counter clock wise viewed at the left side of the engine, and read the lobecenter.

Valve opening,

Turn the crankshaft counterclockwise, when 1mm lift the valve, which called "Opening valve". Keep turn the crankshaft counterclockwise when 1mm lift the valve which called "Closing valve".

Cam lobe,

Turn the crankshaft counterclockwise, when maximum lift the valve, read the timing protractor.

## VM26 Carburetor

Item Nos	Product Names
00-03-0151	Pilot jet, # 10
00-03-0152	Pilot jet, # 12.5
00-03-0153	Pilot jet, # 15
00-03-0154	Pilot jet, # 17.5
00-03-0155	Pilot jet, # 20
00-03-0156	Pilot jet, # 22.5
00-03-0157	Pilot jet, # 25
00-03-0158	Pilot jet, # 27.5
00-03-0159	Pilot jet, # 30



03-03-0321

Item Nos	Product Names
00-03-0060	Main jet, # 100
00-03-0061	Main jet, # 105
00-03-0062	Main jet, # 110
00-03-0063	Main jet, # 115
00-03-0064	Main jet, # 120
00-03-0065	Main jet, # 125
00-03-0066	Main jet, # 130
00-03-0067	Main jet, # 135
00-03-0068	Main jet, # 140
00-03-0069	Main jet, # 145
00-03-0070	Main jet, # 150
00-03-0071	Main jet, # 155
00-03-0072	Main jet, # 160
00-03-0073	Main jet, # 165
00-03-0074	Main jet, # 170
00-03-0075	Main jet, # 175
00-03-0076	Main jet, # 180
00-03-0077	Main jet, # 185
00-03-0078	Main jet, # 190
00-03-0079	Main jet, # 195
00-03-0080	Main jet, # 200
00-03-0081	Main jet, # 210
00-03-0082	Main jet, # 220
00-03-0083	Main jet, # 230
00-03-0084	Main jet, # 240
00-03-0085	Main jet, # 250
00-03-0086	Main jet, # 260

## PE28 Carburetor

Item Nos	Product Names
00-03-0137	Slow jet, 35
00-03-0138	Slow jet, 38
00-03-0139	Slow jet, 40
00-03-0140	Slow jet, 42
00-03-0141	Slow jet, 45
00-03-0142	Slow jet, 48
00-03-0143	Slow jet, 50
00-03-0144	Slow jet, 52
00-03-0145	Slow jet, 55
00-03-0146	Slow jet, 58
00-03-0147	Slow jet, 60
00-03-0148	Slow jet, 62
00-03-0149	Slow jet, 65
00-03-0150	Slow jet, 70




03-03-027

Item Nos	Product Names
00-03-0130	Main jet, #82
00-03-0131	Main jet, #85
00-03-0132	Main jet, #88
00-03-0133	Main jet, #90
00-03-0134	Main jet, #92
00-03-0135	Main jet, #95
00-03-0136	Main jet, #98
00-03-0090	Main jet, #100
00-03-0091	Main jet, #102
00-03-0092	Main jet, #105
00-03-0093	Main jet, #108
00-03-0094	Main jet, #110
00-03-0095	Main jet, #112
00-03-0096	Main jet, #115
00-03-0097	Main jet, #118
00-03-0098	Main jet, #120
00-03-0099	Main jet, #122
00-03-0100	Main jet, #125
00-03-0101	Main jet, #128
00-03-0102	Main jet, #130
00-03-0103	Main jet, #132
00-03-0104	Main jet, #135
00-03-0105	Main jet, #138
00-03-0106	Main jet, #140

Item Nos	Product Names
00-03-0107	Main jet, #142
00-03-0108	Main jet, #145
00-03-0109	Main jet, #148
00-03-0110	Main jet, #150
00-03-0111	Main jet, #152
00-03-0112	Main jet, #155
00-03-0113	Main jet, #158
00-03-0114	Main jet, #160
00-03-0115	Main jet, #162
00-03-0116	Main jet, #165
00-03-0117	Main jet, #168
00-03-0118	Main jet, #170
00-03-0119	Main jet, #172
00-03-0120	Main jet, #175
00-03-0121	Main jet, #178
00-03-0122	Main jet, #180
00-03-0202	Main jet, #182
00-03-0123	Main jet, #185
00-03-0124	Main jet, #188
00-03-0125	Main jet, #190
00-03-0126	Main jet, #192
00-03-0127	Main jet, #195
00-03-0128	Main jet, #198
00-03-0129	Main jet, #200

## High flow filter



03-01-1064	for MIKUNI VM26
03-01-1094	for KEIHIN PE28


## Fuel cock assembly



03-03-001


## Insulator

for VM26



00-03-0210

for PE28



00-03-0211

## Involute throttle set



Outer length: 710 mm

09-02-0230 (Black anodized)

09-02-0232 (Gray metallic anodized)

Outer length: 810 mm

09-02-0231 (Black anodized)

09-02-0233 (Gray metallic anodized)

## Standard high throttle set



09-02-0222 (710 mm in outer length)

09-02-0221 (810 mm in outer length)

## 90-bent high throttle set



09-02-021 (700 mm in outer length)

For more information, please refer to our parts catalog, or log onto our Web site at URL <http://www.takegawa.co.jp>

## Racing C.D.I. Magnet Kit

05-02-0511



Excellent startup performance because of ignition at low revolution. (Excellent start-up by a kick starter)  
Ignition timing adjustable at up to 24 degrees,  
Integral ignition coil with built-in CDI unit,  
Fully-covered stator coil to protect the ignition coil,  
Weight saving:  
R-type 58 rotor: 336 g  
Stator, including cords: 383 g  
Ignition coil, including cords: 370 g  
"ROSSA" (red) as proof of high performance  
No charging functions

### Kick starter arm

(Steel-forged)

(Aluminum-forged)



02-08-0052



09-10-006

(Back step should not be installed.)

### Steel Drive Sprocket



02-05-01 (12T Standard)  
02-05-02 (13T Standard)  
02-05-03 (14T Standard)



02-05-041 (15T Racing)  
02-05-051 (16T Racing)

## Titanium retainer & valve spring Set

01-12-0108



Titanium-alloy retainers are supplied, which is about 30% lighter than the one made of steel.  
This newly designed valve spring has the improved valve response at higher engine revolutions

## Optional camshaft

	D10/10	01-08-0150	Option
	D15/15	01-08-0151	Option
	D25/30	01-08-0152	
	D25/25	01-08-0153	Option
	D30/30	01-08-0154	Option

### Clutch lever assembly



02-01-028 (black)  
02-01-0282 (silver)

### Quick lever ASSY.



02-01-0601

### Aluminum Driven Sprocket



02-07-0635 (35T) 02-07-1225 (25T)  
02-07-0638 (38T) 02-07-1228 (28T)  
02-07-0641 (41T) 02-07-1230 (30T)  
02-07-0642 (42T) 02-07-1233 (33T)  
02-07-0643 (43T) 02-07-1235 (35T)

### Steel Driven Sprocket



02-07-0007 (23T)  
02-07-025 (25T)  
02-07-028 (28T)  
02-07-030 (23T)

## Gear Ratio (Final)

Drive \ Driven	23T	24T	25T	26T	27T	28T	29T	30T	31T	32T	33T	34T	35T	36T
12T	1.91	2.00	2.08	2.17	2.25	2.33	2.42	2.50	2.58	2.67	2.75	2.83	2.92	3.00
13T	1.76	1.84	1.92	2.00	2.08	2.15	2.23	2.31	2.38	2.46	2.54	2.62	2.69	2.77
14T	1.64	1.71	1.79	1.86	1.93	2.00	2.07	2.14	2.21	2.29	2.36	2.43	2.50	2.57
15T	1.53	1.60	1.67	1.73	1.80	1.87	1.93	2.00	2.07	2.13	2.20	2.27	2.33	2.40
16T	1.43	1.50	1.56	1.62	1.68	1.75	1.81	1.87	1.93	2.00	2.06	2.12	2.18	2.25

For more information, please refer to our parts catalog, or log onto our Web site at  
URL <http://www.takegawa.co.jp>

Oil cooler

Compact cool



The oil "Compact Cool" is designed more compact compared to our current oil cooler and the best for mini motorcycles such as Monkey / Gorilla. The oil passage is our Standard Type and the corrugated lower fins are incorporated. This cooler body has an oil cooler plate and guard as standard equipments. In addition, the bracket mounting is integrated with the oil cooler plate so that you can use the oil outlet upside down as well.



3-Fin 4-Line AW  
00-07-0055



4-Fin 5-Line AW  
00-07-0008

Oil cooler		Compact cool	
Outlet	Mounting Position	 Steering Stem mount	
		3Fin 4Line	4Fin 5Line
 Clutch cover	Rubber hose		
	Slimline hose	07-07-0160	07-07-0155

For more information, please refer to our parts catalog, or log onto our Web site at  
URL <http://www.takegawa.co.jp>

## Oil catch tank

(side cover type)



**09-04-032**

Tank capacity : 550 cc

## Racing exhaust system.(10R)



**04-01-0029**

This is the specially made for DOHC had to gain the maximum performance of the engine.  
(Made SUS stainless / for racing only)

## Front fork



**06-01-0728**

30 Front Fork Set w/Disc brake  
(For 10-inch ONLY)

Our original front fork with 30 inner tube increases the stability of stroke by damping force generating mechanism of "free-valve" type and reduces the shock when the front shocks rebound and compress.



**06-02-0015**

Top Bridge & Stem



**06-01-0723**

L / R Front Fork Set

## Rear fork



**06-03-0104** Aluminum Swingarm (12cm-extended)

**06-03-0105** Aluminum Swingarm (16cm-extended)

**06-03-0107** Aluminum Swingarm(16cm-extended·With braced)

Both high rigidity and lightweight, which are both essential for swingarm, have been achieved with the well-balanced structure of our original polygon sectional design and thickness of the material.

Moreover, skillful bending and buff finish are excellent and appeal more than others.

For more information, please refer to our parts catalog, or log onto our Web site at  
URL <http://www.takegawa.co.jp>

## Honda-Made Genuine Shim List

Part Number	Description	Part Number	Description	Part Number	Description
14901 -KT7-000	Tappet shim ( 1.200 )	14946 -KT7-000	Tappet shim ( 2.325 )	14926 -KT7-013	Tappet shim ( 1.825 )
14902 -KT7-000	Tappet shim ( 1.225 )	14947 -KT7-000	Tappet shim ( 2.350 )	14927 -KT7-013	Tappet shim ( 1.850 )
14903 -KT7-000	Tappet shim ( 1.250 )	14948 -KT7-000	Tappet shim ( 2.375 )	14928 -KT7-013	Tappet shim ( 1.875 )
14904 -KT7-000	Tappet shim ( 1.275 )	14949 -KT7-000	Tappet shim ( 2.400 )	14929 -KT7-013	Tappet shim ( 1.900 )
14905 -KT7-000	Tappet shim ( 1.300 )	14950 -KT7-000	Tappet shim ( 2.425 )	14930 -KT7-013	Tappet shim ( 1.925 )
14906 -KT7-000	Tappet shim ( 1.325 )	14951 -KT7-000	Tappet shim ( 2.450 )	14931 -KT7-013	Tappet shim ( 1.950 )
14907 -KT7-000	Tappet shim ( 1.350 )	14952 -KT7-000	Tappet shim ( 2.475 )	14932 -KT7-013	Tappet shim ( 1.975 )
14908 -KT7-000	Tappet shim ( 1.375 )	14953 -KT7-000	Tappet shim ( 2.500 )	14933 -KT7-013	Tappet shim ( 2.000 )
14909 -KT7-000	Tappet shim ( 1.400 )	14954 -KT7-000	Tappet shim ( 2.525 )	14934 -KT7-013	Tappet shim ( 2.025 )
14910 -KT7-000	Tappet shim ( 1.425 )	14955 -KT7-000	Tappet shim ( 2.550 )	14935 -KT7-013	Tappet shim ( 2.050 )
14911 -KT7-000	Tappet shim ( 1.450 )	14956 -KT7-000	Tappet shim ( 2.575 )	14936 -KT7-013	Tappet shim ( 2.075 )
14912 -KT7-000	Tappet shim ( 1.475 )	14957 -KT7-000	Tappet shim ( 2.600 )	14937 -KT7-013	Tappet shim ( 2.100 )
14913 -KT7-000	Tappet shim ( 1.500 )	14958 -KT7-000	Tappet shim ( 2.625 )	14938 -KT7-013	Tappet shim ( 2.125 )
14914 -KT7-000	Tappet shim ( 1.525 )	14959 -KT7-000	Tappet shim ( 2.650 )	14939 -KT7-013	Tappet shim ( 2.150 )
14915 -KT7-000	Tappet shim ( 1.550 )	14960 -KT7-000	Tappet shim ( 2.675 )	14940 -KT7-013	Tappet shim ( 2.175 )
14916 -KT7-000	Tappet shim ( 1.575 )	14961 -KT7-000	Tappet shim ( 2.700 )	14941 -KT7-013	Tappet shim ( 2.200 )
14917 -KT7-000	Tappet shim ( 1.600 )	14962 -KT7-000	Tappet shim ( 2.725 )	14942 -KT7-013	Tappet shim ( 2.225 )
14918 -KT7-000	Tappet shim ( 1.625 )	14963 -KT7-000	Tappet shim ( 2.750 )	14943 -KT7-013	Tappet shim ( 2.250 )
14919 -KT7-000	Tappet shim ( 1.650 )	14964 -KT7-000	Tappet shim ( 2.775 )	14944 -KT7-013	Tappet shim ( 2.275 )
14920 -KT7-000	Tappet shim ( 1.675 )	14965 -KT7-000	Tappet shim ( 2.800 )	14945 -KT7-013	Tappet shim ( 2.300 )
14921 -KT7-000	Tappet shim ( 1.700 )	14901 -KT7-013	Tappet shim ( 1.200 )	14946 -KT7-013	Tappet shim ( 2.325 )
14922 -KT7-000	Tappet shim ( 1.725 )	14902 -KT7-013	Tappet shim ( 1.225 )	14947 -KT7-013	Tappet shim ( 2.350 )
14923 -KT7-000	Tappet shim ( 1.750 )	14903 -KT7-013	Tappet shim ( 1.250 )	14948 -KT7-013	Tappet shim ( 2.375 )
14924 -KT7-000	Tappet shim ( 1.775 )	14904 -KT7-013	Tappet shim ( 1.275 )	14949 -KT7-013	Tappet shim ( 2.400 )
14925 -KT7-000	Tappet shim ( 1.800 )	14905 -KT7-013	Tappet shim ( 1.300 )	14950 -KT7-013	Tappet shim ( 2.425 )
14926 -KT7-000	Tappet shim ( 1.825 )	14906 -KT7-013	Tappet shim ( 1.325 )	14951 -KT7-013	Tappet shim ( 2.450 )
14927 -KT7-000	Tappet shim ( 1.850 )	14907 -KT7-013	Tappet shim ( 1.350 )	14952 -KT7-013	Tappet shim ( 2.475 )
14928 -KT7-000	Tappet shim ( 1.875 )	14908 -KT7-013	Tappet shim ( 1.375 )	14953 -KT7-013	Tappet shim ( 2.500 )
14929 -KT7-000	Tappet shim ( 1.900 )	14909 -KT7-013	Tappet shim ( 1.400 )	14954 -KT7-013	Tappet shim ( 2.525 )
14930 -KT7-000	Tappet shim ( 1.925 )	14910 -KT7-013	Tappet shim ( 1.425 )	14955 -KT7-013	Tappet shim ( 2.550 )
14931 -KT7-000	Tappet shim ( 1.950 )	14911 -KT7-013	Tappet shim ( 1.450 )	14956 -KT7-013	Tappet shim ( 2.575 )
14932 -KT7-000	Tappet shim ( 1.975 )	14912 -KT7-013	Tappet shim ( 1.475 )	14957 -KT7-013	Tappet shim ( 2.600 )
14933 -KT7-000	Tappet shim ( 2.000 )	14913 -KT7-013	Tappet shim ( 1.500 )	14958 -KT7-013	Tappet shim ( 2.625 )
14934 -KT7-000	Tappet shim ( 2.025 )	14914 -KT7-013	Tappet shim ( 1.525 )	14959 -KT7-013	Tappet shim ( 2.650 )
14935 -KT7-000	Tappet shim ( 2.050 )	14915 -KT7-013	Tappet shim ( 1.550 )	14960 -KT7-013	Tappet shim ( 2.675 )
14936 -KT7-000	Tappet shim ( 2.075 )	14916 -KT7-013	Tappet shim ( 1.575 )	14961 -KT7-013	Tappet shim ( 2.700 )
14937 -KT7-000	Tappet shim ( 2.100 )	14917 -KT7-013	Tappet shim ( 1.600 )	14962 -KT7-013	Tappet shim ( 2.725 )
14938 -KT7-000	Tappet shim ( 2.125 )	14918 -KT7-013	Tappet shim ( 1.625 )	14963 -KT7-013	Tappet shim ( 2.750 )
14939 -KT7-000	Tappet shim ( 2.150 )	14919 -KT7-013	Tappet shim ( 1.650 )	14964 -KT7-013	Tappet shim ( 2.775 )
14940 -KT7-000	Tappet shim ( 2.175 )	14920 -KT7-013	Tappet shim ( 1.675 )	14965 -KT7-013	Tappet shim ( 2.800 )
14941 -KT7-000	Tappet shim ( 2.200 )	14921 -KT7-013	Tappet shim ( 1.700 )	14966 -KT7-013	Tappet shim ( 2.825 )
14942 -KT7-000	Tappet shim ( 2.225 )	14922 -KT7-013	Tappet shim ( 1.725 )	14967 -KT7-013	Tappet shim ( 2.850 )
14943 -KT7-000	Tappet shim ( 2.250 )	14923 -KT7-013	Tappet shim ( 1.750 )	14968 -KT7-013	Tappet shim ( 2.875 )
14944 -KT7-000	Tappet shim ( 2.275 )	14924 -KT7-013	Tappet shim ( 1.775 )	14969 -KT7-013	Tappet shim ( 2.900 )
14945 -KT7-000	Tappet shim ( 2.300 )	14925 -KT7-013	Tappet shim ( 1.800 )		