Product number 05-06-0033     Maptation node [1125 (MAS-1000001 ~ ])     (Add-1000001 ~ ])     (Add-100000000000000000000000000000000000	<u>Meter Bracket &amp; Harness Kit(For Super Multi TFT Meter)Instruction manual</u>
These years you very much for purphasing our product. They are used before installation, please deek your always kit contents if there is a point of notice event. Please contact us the dealer of purphase. If the dealer place is a point of notice event. Please contact us the dealer of purphase. If but as information, such as places or illustration different this his part. The use information is the instructions that are written in the small, if the accident or damgs has occurred, we can not assume any reasonibility for comparation. If it is not passed but inputs of the comparation of other samplaturers. If it is not passed but inputs of the comparation of other samplaturers. If it is not passed but inputs of the comparation of other samplaturers. If it is not passed but inputs of the comparation of other samplaturers. If it is not passed but inputs of the comparation of other samplaturers. If you have any such nature. If you have any such nature. If you have any direct have haveling, even if a pation in this product. There is a risk of door incretion of rubber and plactic parts. If you have any direct have haveling, even if a pation in this product. There is a risk of door incretion of rubber and plactic parts. If you have any direct have haveling, even if a place have any direct haveling lowes. If you have any direct haveling, even if a place haveling on the production time. If you have any direct haveling and increases that the have haveling in the same direct. If you have any direct haveling lowes. If you have any direct haveling lowes haveling lowes. If you have any	Product number         05-06-0034         Adaptation model         CT125         (JA55-1000001 ~ )           (JA65-1000001 ~ )         <
<pre>ch Please read carfully before use 1: Bue use ignoring the instruction that are written in the manual, if the accident or damage has occurred, we can not assume any reasonability for componation. Bit is notice that it is a then a problem occurs to after market peods, guarantee other than this product, also on not assume any in any such matters. Bit is not possible to impure of the continuity of other market peods. Bit is not possible to impure of the continuity of other market peods. Bit is not possible to impure of the continuity of other market peods. Bit peods on the other or any olverblicening this product. There is a risk of detorioration of rubber and plastic parts. Bit peods on the other or any olverblicening this product. There is a risk of detorioration of rubber and plastic parts. Bit peods are directly on any olverblicening this product. There is a risk of detorioration of rubber and plastic parts. Bit peods are directly on any olverblicening this product. There is a risk of detorioration of rubber and plastic parts. Bit peods are directly on any olverblicening this product. There is a risk of detorioration of rubber and plastic parts. Bit peods are directly on any olverblicening this product to rubbe part behavious. Bit peods are directly and plastic parts of rubber plastic plastic plastic plastic. Bit peods are directly and plastic plastic plastic plastic plastic plastic plastic plastic. Bit peods are directly and plastic plasti</pre>	Thank you very much for purchasing our products. Thank you so you will comply with the following matters at the time of use. Before installation, please check your always kit contents. If there is a point of notice event, Please contact us the dealer of purchase. <b>© If the description, such as photos or Illustration different with this part.</b>
<ul> <li>Be use jooring the instructions that are written in the manual, if the accident or danage has occurred, we can not assume any margonial bitty for companito.</li> <li>This product installation and use. When a problem occurs to after market goods, guarantee other than this product, also can not assume any margonial bitty for companito.</li> <li>This product installation and use. When a problem occurs to after market goods, guarantee other than this product, also can not assume any margonial bitty for companito.</li> <li>This product installation and use. When a problem occurs to after market goods, guarantee other than this product, also can not assume any margonial bitty of the account of the market goods.</li> <li>This product is the above-mention of other manufacturer.</li> <li>This product is the above-mention device location is provided. The nossible attracted to the other whole. Please note.</li> <li>This product and programs are subject to form any factoring gives: how writhout work gives.)</li> <li>This product and programs are subject to device any factor on the opposite whole.</li> <li>This product and programs are subject to device any factor and the product on the production time.</li> <li>The row has a signal spood to device a state made accuratively for specified vehicle.</li> <li>There may be a signal spood to device any product on the production store.</li> <li>There may be a signal spood to device a specified vehicle.</li> <li>There may be a signal spood to device any product on the production store.</li> <li>The specific grant are subject to the CII25 with a custom bracket and sub-wire included in the kit.</li> <li>The specific grant are subject to the CII25 with a custom bracket and sub-wire included in the kit.</li> <li>The subset while any and etch for large production tap and a signal mark being to the specific product factor on the specific product.</li> <li>The subset while any subject and the specific product and sub-wire included in the kit.</li> <li>The specific subset bracket</li></ul>	☆Please read carefully before use ☆
© This product installation and use, when a problem occurs to after markit goods, guarantoo other than this product, also can not assume any may such matters. It has been proceeded this a product, it will not be covered under warranty. It is not possible to impuire of the combination of other manufacturers. It is not possible to impuire of the combination of other manufacturers. If is not possible to impuire of the combination of other manufacturers. If you have any questions, Bases context your (call lategaes date): Product may have dega or protuinions. Be sure to sear working gloves. This is not use gaoline or thinner (or any solvent) cleaning this product. There is a risk of deterioration of rubber and plastic parts. If you have any gloves this from the sure to sear working gloves. This is not anong flower this from the sure to sear working gloves. Product and program are subject to change and improvement without notice. This orden cannot be used to neares other than and sore mays flattly differ depending on the production time. There is the same product number, the operation and sore mays flattly differ depending on the production time. The same bas all gibt product to defay and the submary of the application atc. The same bas all gibt product to defay and the submary of the application atc. The same bas all gibt product to defay and the submary of the application atc. The same bas all gibt product on Adds. Honds genuine accessory socket: 08070-4282-000 annot be used it self. SP MARSMA Carl and product the attribute to subther. The same bas all gibts to product to the mater body. This socket methor cannot provents vibration to the mater body. This socket methor cannot socket the function at a call all socket and sub-wire included in the kit. Using a auther mount provents with an accental socket and sub-wire included in the kit. Market all and a socket to prove that there to a socket and socket and socket and socket and some socket and socket and socket and socket and socket and socket	The use ignoring the instructions that are written in the manual, if the accident or damage has occurred, we can not assume any responsibility for compensation.
<pre>0 It is not noticities to inquire of the combination of other manufacturer. 0 It is product is the above-mentioned value seclarive goals in not possible attached to the other valuela. Please note. 0 If you have again on thimmer (or any solvent)cleaning this product. There is a risk of detrioration of rubber and plastic parts. 1 If you have any questions, plases contrate your local Takegam dealer. 0 Forbut may ave to any protrain the second to your local Takegam dealer. 0 Forbut may ave to any protrain the second to your local Takegam dealer. 0 Forbut may ave to any protrain the second to your local Takegam dealer. 0 Forbut and programs are subject to change and increvement without notice. 0 Forbut and programs are subject to change and increvement without notice. 0 For using this product on JAGS. Henda genuine accessory socket: OBUP-AKE-JOO cannot be used its seft. 9 For using this product on JAGS. Henda genuine accessory socket: OBUP-AKE-JOO cannot be used its seft. 9 For using this product on JAGS. Henda genuine accessory socket: OBUP-AKE-JOO cannot be used its seft. 9 FAREUMA circuing and increase the socket of the arror cede such as "ABS" may come on but it cannot be erased. (wrow speed display setting is changed) 9 For using this product on JAGS. Henda genuine accessory socket: OBUP-OKE-JOO cannot be used its seft. 9 FAREUMA circuing and the display and its changed is a set any functions such as rotation speed, gear position, thermemoter, battery voltage display, the such and the display and its the function within a notrical settor. 9 For user dismeter correction, power test function, etc. (in addition to speed, ded / trip meter) 10 can an dhage the display and its the adversely affects the digital circuit, resulting in product failure or malfunction. 10 For any and the display and the adversely affects the digital circuit, resulting in product failure or malfunction. 10 For any and display by chassis dynam or free rollers for asafety reasons. 10 For any and display by chassis dy</pre>	<ul> <li>In the product installation and use, when a problem occurs to after market goods, guarantee other than this product, also can not assume any in any such matters.</li> <li>If it was the case or mounting that has been processed like a product, it will not be covered under warranty.</li> </ul>
<ul> <li>(*) Chamme many rest of global provide interms and the first article acher without work global.</li> <li>(*) Chamme many rest of global provide interms of the application of the product of the global provide interms.</li> <li>(*) This is not control build of the many first the source of the source of</li></ul>	<ul> <li>It is not possible to inquire of the combination of other manufacturers.</li> <li>This product is the above-mentioned vehicle exclusive goods. Is not possible attached to the other vehicle. Please note.</li> <li>Do not use gasoline or thinner (or any solvent)cleaning this product. There is a risk of deterioration of rubber and plastic parts.</li> <li>If you have any questions, please contact your local Takegawa dealer.</li> <li>Product may have advect a protection of a plastic parts.</li> </ul>
<pre>® Product and programs are subject to change and improvement without notice. Even with the same product number, the operation and screme may slightly differ depending on the production time.</pre> © There may be a slight speed difference with the GPS of the application etc. © Caution: Some vehicles, when replacing the specket, the error code such as "ABS" may come on but it cannot be ersed. (seen may be display satting is changed). © For using this product on Abds, Honds graunie accessory socket: 08U70-X2E-U00 cannot be used it self. SP IAEGNMM sliger socket bracket: 90 1000 make possible to use together. — Feature ~ The Super Nulti IFT meter can be attached to the CHI2S with a custom bracket and sub-wire included in the kit. Using a rubber mount prevents vibration ot the meter body. The outer dimanter correction, power test function etc. (in addition to speed, dod / trip meter) You can change the display and set the function with an external switch. <b>A totact State Addition A totact State Addition</b> The use LED, H. D. headlights or fog lamps kit made by other than our companies at the same time. Some ballast / inverter (voltage converter) generates high-voltage noise in the site of user display. <b>A totact state adversaly</b> the display lamb are display by chasis dynamo. Free roller or actual driving. <b>A sum of the same flag and state display shales dynamo.</b> Free roller or sately reasons. Do not user generates high-voltage display by chasis dynamo. Free roller or sately reasons. <b>A sum of the outer of the source shale state as a bise with good visibility and obsek the surroundings. A sum of the source shale state of the same state down withe addition dynamic source display. <b>A sum of the source shale state down on the source source shale state down on the source shale state down on the source source shale state down on the source source shale state as a solice the source source shale state s</b></b>	<ul> <li>(Please wear work gloves when working, even if a photo in this article show without work gloves.)</li> <li>(Please wear work gloves when working, even if a photo in this article show without work gloves.)</li> <li>(Please wear work gloves when working, even if a photo in this article show without work gloves.)</li> <li>(Please wear work gloves when working, even if a photo in this article show without work gloves.)</li> <li>(Please wear work gloves when working, even if a photo in this article show without work gloves.)</li> <li>(Please wear work gloves when working, even if a photo in this article show without work gloves.)</li> <li>(Please wear work gloves when working, even if a photo in this article show without work gloves.)</li> <li>(Please wear work gloves when working, even if a photo in this article show without work gloves.)</li> <li>(Please wear work gloves when working, even if a photo in this article show without work gloves.)</li> <li>(Please wear work gloves when working, even if a photo in this article show without work gloves.)</li> <li>(Please wear work gloves when working, even if a photo in this article show without work gloves.)</li> <li>(Please wear work gloves when work gloves when working gloves.)</li> <li>(Please wear work gloves when work gloves when work gloves.)</li> <li>(Please wear work gloves when work gloves when work gloves wear work gloves.)</li> <li>(Please wear work gloves when work gloves wear work gloves.)</li> <li>(Please wear work gloves wear work gloves wear work gloves.)</li> <li>(Please wear work gloves wear work gloves wear work gloves.)</li> <li>(Please wear work gloves wear work gloves wear work gloves wear wear wear wear wear wear wear wear</li></ul>
<ul> <li>© Aution: Same vahiles, when replacing the sprocket, the error code such as "ABS" may come on but it cannot be erased. (evrow speed display sating is chanced)</li> <li>© For using this product on JAGS. Honda genuine accessory socket: 08070-K2E-J000 cannot be used it self. SP TAKEMAA cigar socket bracket: 09-01-0001 make possible to use together.</li> <li>~ feature ~</li> <li>The Super Multi IFT meter can be attached to the G1125 with a custom bracket and sub-wire included in the kit. Using a rubber mount prevents vitration to the meter body.</li> <li>This outcom meter can be equipped a great many functions such as rotation speed, gear position, thermometer, battery voltage display. This outcom meter can be equipped a great many functions such as rotation speed, gear position, thermometer, battery voltage display. This outcom meter can be equipped a great many functions such as rotation speed, gear position, thermometer, battery voltage display. The outcom display and set the function with an external switch.</li> <li>None the meter comes with a stick temperature sensor, you can detect oil temperature with the adding SP Takegawa magnet drain bolt.</li> <li>A ters outcom Multi IFT Meter</li> <li>Do not use LED. H. D. D. headlights or fog lamps kit made by other than our companies at the same time. Some ballast / inverter (voltage converter) generates high-voltage noise that adversely affects the digital circuit, resulting in product failure on the strain gear display on diving in the city because there are many traffol light and traffol in the city.</li> <li>We recommend learning gear display on diving in the cild gial and the agine and the metric in a diving.</li> <li>Metter are display on diving in the cild gial and the engine and the metric is cold). (It may cause highty)</li> <li>Metter are display on diving in the cild gial and the engine and the metric is cold). (It may cause injury.)</li> <li>Metter function, beta time diving the wore of a strain di</li></ul>	© Product and programs are subject to change and improvement without notice. Even with the same product number, the operation and screen may slightly differ depending on the production time. © There may be a slight speed difference with the GPS of the application etc.
<ul> <li>◎ For using this product on JAGS, Honda genuine accessory socket: 08U70-K2E-JOQ cannot be used it self.</li> <li>SP IAKEGAMA ciars socket bracket: 09-01-0001.make possible to use together.</li> <li>~ Feature ~</li> <li>The Super Multi IFT meter can be attached to the GT125 with a custom bracket and sub-wire included in the kit.</li> <li>Ling as tubber mount prevents vibration to the meter body.</li> <li>This custom mater can be equipped a great many functions such as rotation speed, gar position, thermometer, battery voltage display, tire such of mater body.</li> <li>Motel bange be capitod up to test information on external witch.</li> <li>Note:Super Multi IFT Meter</li> <li>Do not use LED. H. D. headlights or fog lamps kit made by other than our companies at the same time. Some ballast / inverter (voltage converter) generates high-voltage noise that adversely affects the digital circuit, resulting in product failure or malfunction.</li> <li>✓ Note: super Multi IFT Mater</li> <li>Do not use LED. H. D. headlights or fog lamps kit made by other than our companies at the same time. Some ballast / inverter (voltage converter) generates high-voltage noise that adversely affects the digital circuit, resulting in product failure or malfunction.</li> <li>✓ Note: super Multi IFT Mater</li> <li>To sto the gae position.</li> <li>To sto the gae position, both the speed signal and the engine soeed signal must be input to the Super Multi DN meter. Therefore, it is require to learn gar display on driving in the oity because dynamo. For oral lor or actual driving.</li> <li>We not the handling of inporing this display, property damage and human shows the assumption of what injury.</li> <li>When performing the work, it should be made to prepare the tools for the job. (Breakage of parts, it may cause injury.)</li> <li>Do the work must always specified torque working. Jease were work gloves to protect your hands, (It may cause injury.)</li> <li>Be po</li></ul>	<ul> <li>Caution: Some vehicles, when replacing the sprocket, the error code such as "ABS" may come on but it cannot be erased. (even speed display setting is changed)</li> </ul>
~ Feature ~     The Super Multi ITT meter can be attached to the CT125 with a custom bracket and sub-wire included in the kit.     Using arubber mount prevents vibration to the meter body.     The Super Multi ITT meter can be autoped a great many functions such as rotation speed, gear position, thermometer, battery voltage display,     tire outer diameter carbe equiped a great many functions such as rotation speed, gear position, thermometer, battery voltage display,     tire outer diameter carbe equiped a great many functions with an external swith.     Since the meter comes with a stick temperature sensor, you can detect oil temperature with the adding SP Takegawa magnet drain bolt.     NoteSuper Multi ITT Meter     Do not use LED.H.I.D. headlights or fog lamps kit made by other than our companies at the same time. Some ballast / inverter (voltage     converter) generates high-voltage noise that adversely affects the digital circuit, resulting in product failure or malfunction.     Note: setting the gear position     To set the gear position to the super Multi DN meter.     Therefore, it is require to learn gar display by chassis dynamo, free roller or astal driving.     We accommend learning gear display by chassis dynamo, there or leng viraffo lights and traffic in the city.     When performing in actual driving, select a safe place with good visibility and check the surroundings.     When performing the work, e.c., be sure during the cold (when the engine and the marker is cold). (It may cause burns.)     When performing the work, to chould be made to prepare the tools for the job. (Breakage of parts, it may cause injury.)     Do the work must always specified torque using a torque weren(. Quange do bolts and nucle, and cause of dropout.)     The product and the frame, might have edges or protusions. When working, please ware work gloves to protect your hands. (It may cause injury,)     Do the work must always specified torque weren(. Quange do bolts and nucle, and cause of thoroput.)     The nord	© For using this product on JA65, Honda genuine accessory socket: 08U70-K2E-J00 cannot be used it self. SP TAKEGAWA cigar socket bracket: 09-01-0001.make possible to use together.
This custom meter can be equipped a great many functions such as rotation speed, gear position, thermometer, battery voltage display, tire outer dimeter correction, power test function, etc. (in addition to speed, odd / trip meter) You can change the display and set the function with an external switch. Since the meter comes with a stick temperature sensor, you can detect oil temperature with the adding SP Takegawa magnet drain bolt.	$\sim$ feature $\sim$ The Super Multi TFT meter can be attached to the CT125 with a custom bracket and sub-wire included in the kit. Using a rubber mount prevents vibration to the meter body.
Since the meter comes with a stick temperature sensor, you can detect oil temperature with the adding SP Takegawa magnet drain bolt.  A NoteSuper Multi TFT Meter  Do not use LED, H. J. D. headlights or fog lamps kit made by other than our companies at the same time. Some ballast / inverter (voltage converter) generates high-voltage noise that adversely affects the digital circuit, resulting in product failure or melfunction.  A Note: setting the gear position  To so the gear position, both the speed signal and the engine speed signal must be input to the Super Multi DN meter.  Therefore, it is require to learn gear display by chassis dynamo. free roller or actual driving.  We recommend learning gear display by chassis dynamo or free roller for safety reasons.  Do not learn gear display by chassis dynamo or free roller for safety reasons.  Do not learn gear display by chassis dynamo or free roller for safety reasons.  Do not learn gear display by chassis dynamo or free roller or actual driving.  Me recommend driving, select a safe place with good visibility and check the surroundings.  Men the handling of ignoring this display, property damage and human shows the assumption of what injury.  Men the handling of ignoring this display, property damage of bulks and nuts, and cause of dropout.)  The product and the frame, might have edges or protrusions. Men working, please wark work gloves to protect your hands. (It may cause injury.)  Be sure to each part inspection before operation, check the loosaning of the threaded portion, be sure of securely tighten the specified torque if there is loose. (It may cause detahement of the parts.)  Men mer mining the work do the work safely stabilize the vehicle in a horizontal location.  (There is a risk of injury vehicle collapsed while working.)  Busined  During operation, when an abnormality occurs, immediately top the vehicle in a harizontal location.  (There is a risk that lead to accidents Continued use.)  Inspection maintenance, there is a risk that result to an accident	This custom meter can be equipped a great many functions such as rotation speed, gear position, thermometer, battery voltage display, tire outer diameter correction, power test function, etc. (in addition to speed, odd / trip meter) You can change the display and set the function with an external switch.
<ul> <li>Note-supper molit information</li> <li>Note-supper molition in the network of the series of the</li></ul>	Since the meter comes with a stick temperature sensor, you can detect oil temperature with the adding SP Takegawa magnet drain bolt.
<ul> <li>A Note: setting the gear position</li> <li>To set the gear position, both the speed signal and the engine speed signal must be input to the Super Multi DN meter. Therefore, it is require to learn gear display by chassis dynamo, free rollers or safety reasons.</li> <li>Do not learn gear display by chassis dynamo or free rollers for safety reasons.</li> <li>Do not learn gear display on driving in the city because there are many traffic lights and traffic in the city. Men performing in actual driving, select a safe place with good visibility and check the surroundings.</li> <li>A Cution Wen the handling of ignoring this display, property damage and human shows the assumption of what injury.</li> <li>When performing the work, etc., be sure during the cold (when the engine and the muffler is cold). (It may cause injury.)</li> <li>Do the work must always specified torque using a torque wrench. (Damage of bolts and nuts, and cause of dropout.)</li> <li>The product and the frame, might have edges or protrusions. When working, please wear work gloves to protect your hands. (It may cause injury.)</li> <li>De sure to each part inspection before operation, check the loosening of the threaded portion, be sure to securely tighten the specified torque if there is loose. (It may cause detachment of the parts.)</li> <li>A wraning When the handling of ignoring this display people died, shows the contents of the serious injury possibility is assued.</li> <li>During operation, when an abnomality occurs, immediately stop the vehicle in a safe place, please stop running. (It may lead to an accident.)</li> <li>Then carrying out the inspection and maintenance, there is a risk that result to an accident.)</li> <li>Then carrying out the inspection and maintenance, etcr., if found damaged parts, replace the damaged parts to avoid possible to reuse the parts (Unrus itable inspection, and maintenance, etc., if found damaged parts, eplace the damaged parts to avoid possible to</li></ul>	Do not use LED, H. I. D. headlights or fog lamps kit made by other than our companies at the same time. Some ballast / inverter (voltage converter) generates high-voltage noise that adversely affects the digital circuit, resulting in product failure or malfunction.
I o set the gear position, both the speed signal and the engine speed signal must be input to the Super Multi DN meter. Therefore, it is require to learn gear display by chassis dynamo. free rollers for safety reasons. Do not learn gear display on driving in the city because there are many traffic lights and traffic in the city. When performing in actual driving, select a safe place with good visibility and check the surroundings. A caution When the handling of ignoring this display, property damage and human shows the assumption of what injury. When performing the work, etc., be sure during the cold (when the engine and the muffler is cold). (It may cause burns.) The product and the frame, might have dages or protrusions. When working, please wear work gloves to protect your hands. (It may cause injury.) De the work must always specified torque using a torque wrench. Qamage of bolts and nuts, and cause of dropout.) The product and the frame, might have dages or protrusions. When working, please wear work gloves to protect your hands. (It may cause injury.) Be sure to each part inspection before operation, check the loosening of the threaded portion, be sure to securely tighten the specified torque if there is loose. (It may cause detachment of the parts.) Wrining When the handling of ignoring this display people died, shows the contents of the serious injury possibility is assumed. I using orderation, when an abnormality occurs, immediately stop the vehicle in a barizontal location. (There is a risk of injury vehicle collapsed while working.) I have to assort parks of using the work, go the working.) I have is days of the inspection and maintenance, etc., if found damaged parts, replace the damaged parts to avoid possible to reuse the parts. (There is a risk that lead to accidents Continued use.) Plastic bass of product packaging, you can either be stored in a place that is out of reach of children, it should be discarded.	Note: setting the gear position
Do not learn gear display on driving in the city because there are many traffic lights and traffic in the city. When performing in actual driving, select a safe place with good visibility and check the surroundings.	To set the gear position, both the speed signal and the engine speed signal must be input to the Super Multi DN meter. Therefore, it is require to learn gear display by chassis dynamo, free roller or actual driving. We recommend learning gear display by chassis dynamo or free rollers for safety reasons.
<ul> <li>A Caution When the handling of ignoring this display, property damage and human shows the assumption of what injury.</li> <li>When performing the work, etc., be sure during the cold (when the engine and the muffler is cold). (It may cause burns.)</li> <li>When performing the work, it should be made to prepare the tools for the job. (Breakage of parts, it may cause injury.)</li> <li>Do the work must always specified torque using a torque wrench. (Damage of bolts and nuts, and cause of dropout.)</li> <li>The product and the frame, might have edges or protrusions. When working, please wear work gloves to protect your hands. (It may cause injury.)</li> <li>Be sure to each part inspection before operation, check the loosening of the threaded portion. be sure to securely tighten the specified torque using a torque are detected.</li> <li>Men the handling of ignoring this display people died, shows the contents of the serious injury possibility is assumed.</li> <li>During operation, when an abnormality occurs, immediately stop the vehicle in a safe place, please stop running. (It may lead to an accident.)</li> <li>When carrying out the inspection and maintenance, there is a risk that result to an accident.)</li> <li>Inspection, maintenance, the inspection and maintenance, etc., if found damaged parts, replace the damaged parts to avoid possible to reuse the parts. (Chere is a risk that lead to accident Sontinued use.)</li> <li>Plastic bags of product packaging, you can either be stored in a place that is out of reach of children, it should be discarded. (When the ABS winthe assertion while driving. (It may lead to an accident.)</li> <li>On once yearse the switch while driving. (It may lead to an accident.)</li> <li>Do not operate the switch while driving. (It may lead to an accident.)</li> <li>Please holdren or wearing. there is a risk of suffocation.)</li> <li>Do not operate the switch while driving. (It may lead to an accident.)</li> <li>On konk</li></ul>	Do not learn gear display on driving in the city because there are many traffic lights and traffic in the city. When performing in actual driving, select a safe place with good visibility and check the surroundings.
<ul> <li>When performing the work, etc., be sure during the cold (when the engine and the muffler is cold). (It may cause burns.)</li> <li>When performing the work, it should be made to prepare the tools for the job. (Breakage of parts, it may cause injury.)</li> <li>Do the work must always specified torque using a torque wrench. (Damage of bolts and nuts, and cause of dropout.)</li> <li>The product and the frame, might have edges or portrusions. When working, please wear work gloves to protect your hands. (It may cause injury.)</li> <li>Be sure to each part inspection before operation, check the loosening of the threaded portion, be sure to securely tighten the specified torque if there is loose. (It may cause detachment of the parts.)</li> <li>Men the handling of ignoring this display people died, shows the contents of the serious injury possibility is assumed.</li> <li>Ouring operation, when an abnormality occurs, immediately stop the vehicle in a safe place, please stop running. (It may lead to an accident.)</li> <li>When performing the work, do the work safely stabilize the vehicle in a horizontal location. (There is a risk of injury vehicle collapsed while working.)</li> <li>Inspection, maintenance, the instruction manual or, inspection methods such as service manuals, to protect the way, should be done correctly. (unsuitable inspection and maintenance, there is a risk that result to an accident.)</li> <li>When carrying out the inspection and maintenance, etc., if found damaged parts, replace the damaged parts to avoid possible to reuse the parts. (There is a risk that lead to accidents Continued use.)</li> <li>Plastic bags of product packaging, you can either be stored in a place that is out of reach of children, it should be discarded. (When the children or wearing, light will light up and ABS will not work. To fix these problems, a vehicle speed signal correction unit is required.</li> <li>Please note. Performance up, the design change, the product and th</li></ul>	Caution When the handling of ignoring this display, property damage and human shows the assumption of what injury.
<ul> <li>Ine product and the frame, might have edges or protrusions. When working, please wear work gloves to protect your hands. (It may cause injury.)</li> <li>Be sure to each part inspection before operation, check the loosening of the threaded portion, be sure to securely tighten the specified torque if there is loose. (It may cause detachment of the parts.)</li> <li>Wen the handling of ignoring this display people died, shows the contents of the serious injury possibility is assumed.</li> <li>During operation, when an abnormality occurs, immediately stop the vehicle in a safe place, please stop running. (It may lead to an accident.)</li> <li>When performing the work, do the work safely stabilize the vehicle in a horizontal location. (There is a risk of injury vehicle collapsed while working.)</li> <li>Inspection, maintenance, the instruction manual or, inspection methods such as service manuals, to protect the way, should be done correctly. (unsuitable inspection and maintenance, etc., if found damaged parts, replace the damaged parts to avoid possible to reuse the parts. (There is a risk that lead to accidents Continued use.)</li> <li>Plastic bags of product packaging, you can either be stored in a place that is out of reach of children, it should be discarded. (When the children or wearing. (It may lead to an accident.)</li> <li>Do not operate the switch while driving. (It may lead to an accident.)</li> <li>On Monkey 125, changed from stock sprocket teeth, an error will occur in the display of the genuine speedometer. (Will show error code.) Also, the ABS warning light will light up and ABS will not work. To fix these problems, a vehicle speed signal correction unit is required. We do not sell vehicle speed signal correction units.</li> <li>Please note. Performance up, the design change, the product and the price in the cost up, etc. are subject to change without notice.</li> <li>Please be informed that we shall be held harnless against any claim against us whatsoever arising out of use of the products i</li></ul>	<ul> <li>When performing the work, etc., be sure during the cold (when the engine and the muffler is cold). (It may cause burns.)</li> <li>When performing the work, it should be made to prepare the tools for the job. (Breakage of parts, it may cause injury.)</li> <li>Do the work must always specified torque using a torque wrench. (Damage of bolts and nuts, and cause of dropout.)</li> </ul>
<ul> <li>Warning When the handling of ignoring this display people died, shows the contents of the serious injury possibility is assumed.</li> <li>During operation, when an abnormality occurs, immediately stop the vehicle in a safe place, please stop running. (It may lead to an accident.)</li> <li>When performing the work, do the work safely stabilize the vehicle in a horizontal location. (There is a risk of injury vehicle collapsed while working.)</li> <li>Inspection, maintenance, the instruction manual or, inspection methods such as service manuals, to protect the way, should be done correctly. (unsuitable inspection and maintenance, there is a risk that result to an accident.)</li> <li>When carrying out the inspection and maintenance, etc., if found damaged parts, replace the damaged parts to avoid possible to reuse the parts. (There is a risk that lead to accidents Continued use.)</li> <li>Plastic bags of product packaging, you can either be stored in a place that is out of reach of children, it should be discarded. (When the children or wearing, there is a risk of suffocation.)</li> <li>Do not operate the switch while driving. (It may lead to an accident.)</li> <li>On Monkey 125, changed from stock sprocket teeth, an error will occur in the display of the genuine speedometer. (Will show error code.) Also, the ABS warning light will light up and ABS will not work. To fix these problems, a vehicle speed signal correction unit is required. We do not sell vehicle speed signal correction units.</li> <li>O Please note. Performance up, the design change, the product and the price in the cost up, etc. are subject to change without notice.</li> <li>Please be informed that we shall be held harmless against any claim against us whatsoever arising out of use of the products in racing and the like.</li> <li>Keep this manual stored until this product is discarded.</li> <li>SPECILPARTS</li> <li>CONTACT Address : 3-5-16 Nishikiorihigashi Tondabayashi Osaka JAPAN IEL: +81</li></ul>	<ul> <li>The product and the frame, might have edges or protrusions. When working, please wear work gloves to protect your hands. (It may cause injury.)</li> <li>Be sure to each part inspection before operation, check the loosening of the threaded portion, be sure to securely tighten the specified torque if there is loose. (It may cause detachment of the parts.)</li> </ul>
<ul> <li>During operation, when an abnormality occurs, immediately stop the vehicle in a safe place, please stop running. (It may lead to an accident.)</li> <li>When performing the work, do the work safely stabilize the vehicle in a horizontal location. (There is a risk of injury vehicle collapsed while working.)</li> <li>Inspection, maintenance, the instruction manual or, inspection methods such as service manuals, to protect the way, should be done correctly. (unsuitable inspection and maintenance, there is a risk that result to an accident.)</li> <li>When carrying out the inspection and maintenance, etc., if found damaged parts, replace the damaged parts to avoid possible to reuse the parts. (There is a risk that lead to accidents Continued use.)</li> <li>Plastic bags of product packaging, you can either be stored in a place that is out of reach of children, it should be discarded. (When the children or wearing, there is a risk of suffocation.)</li> <li>Do not operate the switch while driving. (It may lead to an accident.)</li> <li>On Monkey 125, changed from stock sprocket teeth, an error will occur in the display of the genuine speedometer. (Will show error code.) Also, the ABS warning light will light up and ABS will not work. To fix these problems, a vehicle speed signal correction unit is required. We do not sell vehicle speed signal correction units.</li> <li>Please note. Performance up, the design change, the product and the price in the cost up, etc. are subject to change without notice.</li> <li>Please be informed that we shall be held harmless against any claim against us whatsoever arising out of use of the products in racing and the like.</li> <li>Keep this manual stored until this product is discarded.</li> </ul>	Warning When the handling of ignoring this display people died, shows the contents of the serious injury possibility is assumed.
<ul> <li>Inspection, maintenance, the instruction manual or, inspection methods such as service manuals, to protect the way, should be done correctly. (unsuitable inspection and maintenance, there is a risk that result to an accident.)</li> <li>When carrying out the inspection and maintenance, etc., if found damaged parts, replace the damaged parts to avoid possible to reuse the parts. (There is a risk that lead to accidents Continued use.)</li> <li>Plastic bags of product packaging, you can either be stored in a place that is out of reach of children, it should be discarded. (When the children or wearing, there is a risk of suffocation.)</li> <li>Do not operate the switch while driving. (It may lead to an accident.)</li> <li>On Monkey 125, changed from stock sprocket teeth, an error will occur in the display of the genuine speedometer. (Will show error code.) Also, the ABS warning light will light up and ABS will not work. To fix these problems, a vehicle speed signal correction unit is required. We do not sell vehicle speed signal correction units.</li> <li>Please note. Performance up, the design change, the product and the price in the cost up, etc. are subject to change without notice.</li> <li>Please be informed that we shall be held harmless against any claim against us whatsoever arising out of use of the products in racing and the like.</li> <li>Keep this manual stored until this product is discarded.</li> </ul>	<ul> <li>During operation, when an abnormality occurs, immediately stop the vehicle in a safe place, please stop running. (It may lead to an accident.)</li> <li>When performing the work, do the work safely stabilize the vehicle in a horizontal location. (There is a risk of injury vehicle collapsed while working.)</li> </ul>
<ul> <li>the parts. (There is a risk that lead to accidents Continued use.)</li> <li>Plastic bags of product packaging, you can either be stored in a place that is out of reach of children, it should be discarded. (When the children or wearing, there is a risk of suffocation.)</li> <li>Do not operate the switch while driving. (It may lead to an accident.)</li> <li>On Monkey 125, changed from stock sprocket teeth, an error will occur in the display of the genuine speedometer. (Will show error code.) Also, the ABS warning light will light up and ABS will not work. To fix these problems, a vehicle speed signal correction unit is required. We do not sell vehicle speed signal correction units.</li> <li>Please note. Performance up, the design change, the product and the price in the cost up, etc. are subject to change without notice.</li> <li>Please be informed that we shall be held harmless against any claim against us whatsoever arising out of use of the products in racing and the like.</li> <li>Keep this manual stored until this product is discarded.</li> </ul>	<ul> <li>Inspection, maintenance, the instruction manual or, inspection methods such as service manuals, to protect the way, should be done correctly. (unsuitable inspection and maintenance, there is a risk that result to an accident.)</li> <li>When carrying out the inspection and maintenance, etc. if found damaged parts, replace the damaged parts to avoid possible to reuse.</li> </ul>
<ul> <li>Do not operate the switch while driving. (It may lead to an accident.)</li> <li>Do not operate the switch while driving. (It may lead to an accident.)</li> <li>On Monkey 125, changed from stock sprocket teeth, an error will occur in the display of the genuine speedometer. (Will show error code.) Also, the ABS warning light will light up and ABS will not work. To fix these problems, a vehicle speed signal correction unit is required. We do not sell vehicle speed signal correction units.</li> <li>O Please note. Performance up, the design change, the product and the price in the cost up, etc. are subject to change without notice.</li> <li>O Please be informed that we shall be held harmless against any claim against us whatsoever arising out of use of the products in racing and the like.</li> <li>O Keep this manual stored until this product is discarded.</li> <li>SPECIAL PARIS</li> <li>CONTACT Address : 3-5-16 Nishikiorihigashi Tondabayashi Osaka JAPAN TEL: +81-721-25-1357 FAX:+81-721-24-5059 e-mail:english@takegawa.co.jp URL http://www.takegawa.co.jp</li> </ul>	the parts. (There is a risk that lead to accidents Continued use.) Plastic bags of product packaging, you can either be stored in a place that is out of reach of children, it should be discarded. (When the children error meaning, there is a risk of auffection)
<ul> <li>Please note. Performance up, the design change, the product and the price in the cost up, etc. are subject to change without notice.</li> <li>Please be informed that we shall be held harmless against any claim against us whatsoever arising out of use of the products in racing and the like.</li> <li>Keep this manual stored until this product is discarded.</li> <li>SPECIAL PARTS</li> <li>CONTACT Address: 3-5-16 Nishikiorihigashi Tondabayashi Osaka JAPAN</li> <li>TEL: +81-721-25-1357 FAX:+81-721-24-5059 e-mail:english@takegawa.co.jp</li> <li>URL http://www.takegawa.co.jp</li> </ul>	<ul> <li>Do not operate the switch while driving. (It may lead to an accident.)</li> <li>On Monkey 125, changed from stock sprocket teeth, an error will occur in the display of the genuine speedometer. (Will show error code.) Also, the ABS warning light will light up and ABS will not work. To fix these problems, a vehicle speed signal correction unit is required. We do not sell vehicle speed signal correction units.</li> </ul>
SPECIAL PARTS CONTACT Address : 3-5-16 Nishikiorihigashi Tondabayashi Osaka JAPAN TEL: +81-721-25-1357 FAX:+81-721-24-5059 e-mail:english@takegawa.co.jp URL http://www.takegawa.co.jp	<ul> <li>Please note. Performance up, the design change, the product and the price in the cost up, etc. are subject to change without notice.</li> <li>Please be informed that we shall be held harmless against any claim against us whatsoever arising out of use of the products in racing and the like.</li> <li>Keep this manual stored until this product is discarded.</li> </ul>
	SPECIAL PARTS CONTACT Address : 3-5-16 Nishikiorihigashi Tondabayashi Osaka JAPAN TEL: +81-721-25-1357 FAX:+81-721-24-5059 e-mail:english@takegawa.co.jp URL http://www.takegawa.co.jp





2

\* Please order in the repair parts are always repair part number. If it is not the part number order, you may not be able to order. Please be forewarned.

It should be noted, In the case of parts that can not be separately shipment.

please order a set part number % Repair parts may differ slightly from the kit contents in terms of shape, etc.

There is no problem to use it. Please be forewarned. %(3) Cushion rubber is already assembled on the (9) meter bracket. % The repair parts for the (8) Oz sensor connection cord are different from the kit accessories and are non-waterproof



16

Cable tie 300mm





2024.1.19



2024. 1. 19





2024. 1. 19

05-06-0034 7/8

