

Steering Stem Nut Instruction manual

Product number 06-02-0011

Adaptation
model

For Honda Mini Moto (screw diameter M22 pitch 1.0 depth 12.5)
Monkey · Gorilla · DAX · Ape50/100 · XR50/100Motard ·
Magna50 · JAZZ · Dream50 · CD50/BENLY50S ·
SOLO · BENLY · CD125T · NSR50/80 · NS50F · CRF50/70 ·
XR50/70R/Gixxer · GSX-R125

Thank you very much for purchasing our products.

Thank you so you will comply with the following matters at the time of use. Before installation, please check your always kit contents. If there is a point of notice event, Please contact us the dealer of purchase.

◎ If the description, such as photos or illustration different with this part.

☆ Please read carefully before use ☆

- ◎ The use ignoring the instructions that are written in the manual, if the accident or damage has occurred, we can not assume any responsibility for compensation.
- ◎ This product installation and use, when a problem occurs to after market goods, guarantee other than this product, also can not assume any in any such matters.
- ◎ Installation of product, go to ensure reference to a genuine service manual to adaptive models always.
- ◎ If it was the case or mounting that has been processed like a product, it will not be covered under warranty.
- ◎ It is not possible to inquire of the combination of other manufacturers.
- ◎ This product is the above-mentioned vehicle exclusive goods. Is not possible attached to the other vehicle. Please note.

~ feature ~

- This steering stem nut is made of billet duralumin with an alumite-treated surface.
Therefore, you can dress up your motorcycle quite easily just by changing the stock stem nut with this one.
- As a fuel preserve tube will be inserted into the stem on CRF50F and other models, we have made a recess on the rear side of the stem nut as a locating hole to make the drilling of a hole easy.


**SPECIAL PARTS
TAKEGAWA**

CONTACT Address : 3-5-16 Nishikiorihigashi Tondabayashi Osaka JAPAN

TEL: +81-721-25-1357 FAX: +81-721-24-5059

e-mail: english@takegawa.co.jp URL http://www.takegawa.co.jp

Please contact with your name and country name provided. (Only English please)



Caution

When the handling of ignoring this display, property damage and human shows the assumption of what injury.

- When performing the work, it should be made to prepare the tools for the job. (Breakage of parts, it may cause injury.)
- Do the work must always specified torque using a torque wrench. (Damage of bolts and nuts, and cause of dropout.)
- The product and the frame, might have edges or protrusions. Please go to protect your hands when you work. (It may cause injury.)
- Be sure to each part inspection before operation, check the loosening of the threaded portion, be sure to securely tighten the specified torque if there is loose. (It may cause detachment of the parts.)



Warning

When the handling of ignoring this display people died, shows the contents of the serious injury possibility is assumed.

- During operation, when an abnormality occurs, immediately stop the vehicle in a safe place, please stop running. (It may lead to an accident.)
- When performing the work, do the work safely stabilize the vehicle in a horizontal location. (There is a risk of injury vehicle collapsed while working.)

◎ Please note. Performance up, the design change, the product and the price in the cost up, etc. are subject to change without notice.

◎ Please be informed that we shall be held harmless against any claim against us whatsoever arising out of use of the products in racing and the like.

◎ Keep this manual stored until this product is discarded.

Product content



Product content	Quantity
Steering stem nut	1

Mounting procedure

※ Please refer to the genuine service manual if the detail is not mentioned method and the specified torque.

- ◇ With reference to the service manual, remove a stock stem nut and stem nut washer.
- Place the stock stem nut washer onto the stem, and tighten the steering stem nut to the specified torque.

▲ Note: Be sure that you protect specified torque.
Steering stem nut
Torque : 60N · m (6.0kgf · m)